

Fire Plenum Cable Shielded - FPLP



Product Description: Multi-conductor, insulated and jacket with smoke & flame resistant compound; twisted for maximum flexibility and jacketed with a fire retardant compound. Meets article NEC 760-4 (D).

UL Standard 1424 Fifth Edition February 16, 2007
Meets NEC Article 760 & California Fire Marshall Requirements.

Application: For use in air plenums without conduit for fire and burglar alarm systems, fire control, smoke detection, communication and related fire control systems in accordance.

P/N	AWG	COND	INS THICKNESS	JACKET THICKNESS	NOM DIA.	NOM. CAP. PF/FT	APPROX WEIGHT / M
660218	18	2	.008	.014	.153	55	18
660418	18	4	.008	.014	.164	55	30
660618	18	6	.008	.014	.188	55	42
660216	16	2	.008	.014	.177	62	25
660416	16	4	.008	.014	.191	62	43
660616	16	6	.008	.014	.219	62	62
660214	14	2	.008	.014	.206	64	36
660414	14	4	.008	.014	.222	64	65
660212	12	2	.008	.014	.241	71	53

These values are nominal in accordance with industry standards. Additional gauges, colors or stranding are available upon request with minimum purchase orders.

Color Code Chart # 3

Standard Jacket Color - Red
Voltage - 300V Max
Temperature -20° to 75°C

Available in 500 or 1000'
Boxes, Spools or Coil Packs



FALCON FINE WIRE AND WIRE PRODUCTS, INC.
2401 DISCOVERY BLVD • ROCKWALL, TEXAS 75032
214-771-3441 • 972-722-9168 • falconwire@aol.com