

IMSA 19-3 14AWG



Product Description: 2 or more bare copper conductors conforming to ASTM B-3 before insulating. Insulated with Polyethylene (per UL 62, ASNI C33.1 except for cold bend test shall be minus 55°C). Twisted with overall clear binder mylar tape at least 15% of its width. Jacketed with a high quality Class 2 PVC (per UL 62 ANSI C33.1).

Sunlight resistant (per UL 854 ANSI C33.51)

Rated at 600V Indent printed

Non-wicking, non-metallic moisture resistant fillers are used when needed to make round

This cable is run in a figure 8 Type construction with a messenger for support in aerial installations.

USE: Cable may be used as aerial cable when supported by a messenger. This cable can be used as fire protective signaling or traffic signal cable.

Suitable for use in wet or dry locations at 75°C

P/N	AWG	# COND	STRAND	INS THICKNESS	JACKET THICKNESS	Web Thick High	
98021419-3	14	2	SOLID	.025	.045 X .045	.075	.100
980214X19-3	14	2	STRANDED	.025	.045 X .045	.075	.100
98031420-3	14	3	SOLID	.025	.045 X .045	.075	.100
980314X19-3	14	3	STRANDED	.025	.045 X .045	.075	.100
98041419-3	14	4	SOLID	.025	.045 X .045	.075	.100
980414X19-3	14	4	STRANDED	.025	.045 X .045	.075	.100
98051419-3	14	5	SOLID	.025	.045 X .045	.075	.100
980514X19-3	14	5	STRANDED	.025	.045 X .045	.075	.100
98071419-3	14	7	SOLID	.025	.045 X .045	.075	.100
980714X19-3	14	7	STRANDED	.025	.045 X .045	.075	.100
98091419-3	14	9	SOLID	.025	.060 X .045	.075	.100
980914X19-3	14	9	STRANDED	.025	.060 X .045	.075	.100
98101419-3	14	10	SOLID	.025	.060 X .045	.075	.100
981014X19-3	14	10	STRANDED	.025	.060 X .045	.075	.100
98121419-3	14	12	SOLID	.025	.060 X .045	.075	.100
981214X19-3	14	12	STRANDED	.025	.060 X .045	.075	.100
98161419-3	14	16	SOLID	.025	.060 X .045	.075	.100
981614X19-3	14	16	STRANDED	.025	.060 X .045	.075	.100
98201419-3	14	20	SOLID	.025	.060 X .045	.075	.100
982014X19-3	14	20	STRANDED	.025	.060 X .045	.075	.100

These values are nominal in accordance with industry standards.

Additional gauges and conductor count available.

Additional color code and State specific specs available upon request.

Color Code Chart: 4

Voltage: 600V

Temperature: 75°C

