

IMSA 28-3



Product Description: High density polyethylene, 30% conductivity copper covered steel line wire.

USE: For use in signal systems.
Rated at 600V Indent printed

P/N	AWG	COND	STRAND	INSULATION THICKNESS	NOM DIA
98010428-3	4	1	SOLID	.045	.295
98010628-3	6	1	SOLID	.045	.253
98010828-3	8	1	SOLID	.045	.220
98010928-3	9	1	SOLID	.030	.175
98011028-3	10	1	SOLID	.030	.163
98011028-3	12	1	SOLID	.030	.141

These values are nominal in accordance with industry standards.

Color Code: Black

Voltage: 600V

Temperature: 75°C

IMSA 28-4

Product Description: High density PVC, 30% conductivity steel line wire.

USE: For use in signal systems.
Rated at 600V Indent printed

P/N	AWG	COND	STRAND	INSULATION THICKNESS	NOM DIA
98010428-4	4	1	SOLID	.045	.295
98010628-4	6	1	SOLID	.045	.253
98010828-4	8	1	SOLID	.045	.220
98010928-4	9	1	SOLID	.030	.175
98011028-4	10	1	SOLID	.030	.163
98011028-4	12	1	SOLID	.030	.141

These values are nominal in accordance with industry standards

Color Code: Black

Voltage: 600V

Temperature: 75°C



FALCON FINE WIRE AND WIRE PRODUCTS, INC.
2401 DISCOVERY BLVD • ROCKWALL, TEXAS 75032
214-771-3441 • 972-722-9168 • falconwire@aol.com