

# Zip CL2R & FPLR



**Product Description:** Two conductors extruded into a parallel construction that when they are pulled apart they zip down the middle

UL Standard 44 Forth Edition July 11, 2008  
 Revision July 17, 2008  
 Meets NEC Article 725 Conforms to UL 1666 Flame rating

**Application:** Alarm controls, intercom systems.

## CL2R

P/N	AWG	COND	INS THICKNESS	NOM DIA.	NOM. CAP. PF/FT	APPROX WEIGHT / M
430222R	22	2	.018	.065 X .140	15	12
430220R	20	2	.018	.073 X .156	17	16
430218R	18	2	.018	.086 X .182	20	25
430216R	16	2	.018	.096 X .202	21	23

## FPLR

P/N	AWG	COND	INS THICKNESS	NOM DIA.	NOM. CAP. PF/FT	APPROX WEIGHT / M
440216R	18	2	.020	.080 X .164	17	15
440216R	16	2	.020	.095 X .202	17	23
440214R	14	2	.020	.115 X .240	17	32

These values are nominal in accordance with industry standards.  
 Additional gauges, colors or stranding are available upon request with minimum purchase orders.

Standard Jacket Color – CL2R White  
 FPLR Red

Voltage - 300V Max  
 Temperature –20° to 60°C

Available in 500' or 1000'  
 Boxes, Spools or Coil Packs



FALCON FINE WIRE AND WIRE PRODUCTS, INC.  
 2401 DISCOVERY BLVD • ROCKWALL, TEXAS 75032  
 214-771-3441 • 972-722-9168 • falconwire@aol.com