

# Plenum Cables

## Non Shielded - CMP



**Product Description:** Multi-conductor, insulated and jacket with smoke & flame resistant compound; twisted for maximum flexibility.  
 Meets article NEC 725-2 (B), Class 2 circuits.  
 UL Standard 444 Forth Edition July 11, 2008  
 Revision July 17, 2008  
 Meets NEC Article 725 & 800.

**Application:** For use in air plenums without conduit for burglar alarm systems, computers, remote signaling, control and power limited circuits.

P/N	AWG	COND	INS THICKNESS	JACKET THICKNESS	NOM DIA.	NOM. CAP. PF/FT	APPROX WEIGHT / M
*670222	22	2	.008	.013	.116	24	6
*670422	22	4	.008	.013	.124	24	9
*670218	18	2	.008	.013	.149	30	17
*670418	18	4	.008	.013	.160	30	28
630222	22	2	.008	.013	.127	24	9
630422	22	4	.008	.013	.136	24	15
630622	22	6	.008	.013	.156	24	21
630822	22	8	.008	.013	.176	24	27
631022	22	10	.008	.013	.193	24	32
631222	22	12	.008	.013	.209	24	38
630220	20	2	.008	.013	.145	27	12
630420	20	4	.008	.013	.156	27	21
630620	20	6	.008	.013	.178	27	30
630820	20	8	.008	.013	.202	27	40
631020	20	10	.008	.013	.223	27	52
631220	20	12	.008	.013	.241	27	65
630218	18	2	.008	.013	.162	30	17
630318	18	3	.008	.013	.169	30	23
630418	18	4	.008	.013	.175	30	29
630618	18	6	.008	.013	.201	30	42
630818	18	8	.008	.013	.228	30	55
631018	18	10	.008	.013	.252	30	68
631218	18	12	.008	.013	.272	30	80
630216	16	2	.008	.013	.188	33	24
630416	16	4	.008	.013	.195	33	43
630616	16	6	.008	.013	.203	33	64
630214	14	2	.008	.013	.222	34	35
630414	14	4	.008	.013	.231	34	64
630212	12	2	.008	.013	.264	34	51

These values are nominal in accordance with industry standards. Additional gauges, colors or stranding are available upon request with minimum purchase orders.

Color Code Chart # 2      \*SOL BC

Standard Jacket Color – White  
 Voltage - 300V Max  
 Temperature –20° to 75°C

Available in 500' or 1000'  
 Boxes, Spools or Coil Packs

