

Coax and Camera Cable



Temperature 75°C
Standard Black Jacket

P/N	TYPE	CENTER CONDUCTOR	% BRAID	JKT	NOM DIA.	UL
342095	RG 59	20 Solid BC	95% BC	PVC	.242	CL2 Style 1354
342295	RG 59	22 Strand BC	95% BC	PVC	.242	CL2 Style 1354
342095182	RG 59 18/2 COMBO (18/2)	20 Solid BC Strand BC	95% BC	PVC	.275 X .400	CL2
342095182SIAM	RG 59 18/2 SIAMESE (18/2)	20 Solid BC Strand BC	95% BC	PVC	.245 X .460	CL2
341397	RG213	13 Strand BC	96% BC	PVC	.405	Style 1354
341695	RG8X	16 Strand BC	95% BC	PVC	.242	Style 1354
341995	RG58	20 Strand TC	95% TC	PVC	.193	CL2 Style 1354
3420295163	RG59 Combo (16/3)	20 Solid BC Strand BC	2@98% TC	PVC	.364 x .390	Non -UL
342095185KG	RG59 (18/5)	20 Solid BC Strand BC	95% BC Alum tape	PVC	.328 x .584	CMR
342095PE186	RG59 Type (18/5)	20 Solid BC Strand BC	95% BC	PVC	.302 x .529	Non-UL
342295M	RG59	22 Strand BC	95% BC	PVC	.238	Style 1354
342295S	RG59	22 Solid BC	95% BC	PVC	.242	CL2 Style 1354
3420295	RG59U	20 Solid BC	2@98% TC	PE	.305	Non-UL
342095185	RG59 Combo (18/5)	20 Solid BC	95% BC	PVC	.575 x .330	CMR

Water block tape coax cable available upon request
Special make and state specs available